



## Gas Door Installation Instructions

Replaces Part #s FD101A, FD101AL, FD101B, FD101BL

### Parts List

- 1 – Gas Door
- 1 – Keys (for Locking Models)
- 4 - #4 x.025” Self-Tapping Stainless Screws

### Installation

1. Place gas door over filler opening so the door opens toward the front of the vehicle.
2. Apply firm pressure to keep the gas door against the side of the vehicle. Insert the screws, one at a time, starting with the top hole of the door. Then proceed in a clockwise manner to the next hole. The screws will penetrate the plastic housing directly in the center of the ring. Do not over tighten.



*While every attempt is made to ensure that the information contained in these instructions is correct, no liability can be accepted by the authors for loss, damage, or injury caused by any errors in, or omissions from the information given. All service should be performed by qualified mechanics. Crown Automotive Sales Co., Inc. cannot be held responsible for any mechanical work performed. Standard and accepted safety precautions should be used in every procedure.*



## Gas Door Installation Instructions

Replaces Part #s FD101A, FD101AL, FD101B, FD101BL

### Parts List

- 1 – Gas Door
- 1 – Keys (for Locking Models)
- 4 - #4 x .025” Self-Tapping Stainless Screws

### Installation

3. Place gas door over filler opening so the door opens toward the front of the vehicle.
4. Apply firm pressure to keep the gas door against the side of the vehicle. Insert the screws, one at a time, starting with the top hole of the door. Then proceed in a clockwise manner to the next hole. The screws will penetrate the plastic housing directly in the center of the ring. Do not over tighten.



*While every attempt is made to ensure that the information contained in these instructions is correct, no liability can be accepted by the authors for loss, damage, or injury caused by any errors in, or omissions from the information given. All service should be performed by qualified mechanics. Crown Automotive Sales Co., Inc. cannot be held responsible for any mechanical work performed. Standard and accepted safety precautions should be used in every procedure.*