



RT Off-Road LED Tail Light Set Installation Instructions Part #: RT28111 & RT28112

Improve the looks of any JK Wrangler with an LED Tail Light Set from RT Off-Road. These tail lights are a plug-and-play design without the need for anti-flicker or hyper flash modules to function properly. Each light features 36 LED's for improved bulb life over the OE incandescent bulbs and increased brightness.

Kit Contents

- 1 – Left LED Tail Light
- 1 – Right LED Tail Light

Ensure that all components in kit are accounted for.



1. Remove the OE tail lights from the body by removing only the inboard screws and sliding the tail lights inward. Retain screws for installation.
2. Rotate each light socket counterclockwise, remove the socket, and remove the bulbs. Put the OE tail lights aside.
3. Connect the LED tail light wiring to the body. The black wires and "GRD" text on each socket should connect to the wires with the "-" stickers on the tail lights. The body side socket with 2 positive (white) wires should connect to the tail light socket with 2 "+" stickers. (See Figure 1). Connecting the wiring improperly will result in blown fuses to blow and lights to not function.
4. Install the light socket into the tail light and twist it clockwise until it is fully locked into place.
5. Install the LED tail lights onto the vehicle, slide them outward into place, and mount them using the factory screws.



While every attempt is made to ensure that the information contained in these instructions is correct, no liability can be accepted by the authors for loss, damage, or injury caused by any errors in, or omissions from the information given. All service should be performed by qualified mechanics. Crown Automotive Sales Co., Inc. cannot be held responsible for any mechanical work performed. Standard and accepted safety precautions should be used in every procedure.